

## **ONLY TIMERS RANGE**

### **AH5N MULTI RANGE MULTI VOLTAGE**

#### **Features**

1 second to 600 hours time range,  
Programmable by dip switches  
24/240V AC/DC operating voltage,  
One timed and one user selectable set of contacts,  
Supplied with Base, Surface mounting kit available [Y50]

#### **Description**

Full time range 1s,10s,1m, 10m, 1h, 10h, 60h, 600h, Rated voltage 24 to 240 volts AC/DC, Contact rating 5 Amps AC resistive, Reset timing - 0.2 seconds, Power consumed 2VA, Mounting base PF083A, Surface mounting kit Y50 & P3G-08, Size 48mm x 48mm x 84mm



### **AH5F TRUE OFF DELAY TIMER**

#### **Features**

True off delay timer  
Times out after power is removed  
One set of change over contacts

#### **Description**

Rated Voltage 240 Volts AC, Time Range 60 seconds or 30 minutes,  
Contact 1 change over, Contact rating 5 amps, Reset time 0.3 seconds,  
Size 48mm X 48mm X 84mm, Base PF085A



**5 PHILLIPS ST  
THEBARTON S.A. 5031**

**PH (08) 8234 1207  
FAX (08) 8234 1206  
EMAIL [eltron@bigpond.net.au](mailto:eltron@bigpond.net.au)**



## **ONLY TIMERS RANGE**

### **AH3-RA MULTI RANGE**

#### **Features**

Multiple time ranges  
Programmable by dip switches  
Time ranges from 1 second to 10 minutes  
24/240V AC/DC operating voltage  
One timed and one user selectable set of contacts  
Supplied with Base, Surface mounting kit available [Y40]

#### **Description**

Full time range 1s,10s,1m, 10m, Rated voltage 24 to 240 volts AC/DC  
Contact rating 5 Amps AC resistive, Reset time 0.1 seconds, Power  
consumed 2VA, Mounting base PFO83A, Surface mounting kit Y40 &  
P3G-08, Size 58mm x 40mm x 57.5mm



### **AH3-RC MULTI RANGE**

#### **Features**

Multiple time ranges  
Programmable by dip switches  
Time ranges from 6 seconds to 60 minutes  
24/240V AC/DC operating voltage  
One timed and one user selectable set of contacts  
Supplied with Base, Surface mounting kit available [Y40]

#### **Description**

Full time range 6s, 60s, 6m, 60m, Rated voltage 24 to 240 volts AC/DC  
Contact rating 5 Amps AC resistive, Reset time 0.1 seconds  
Power consumed 2VA, Mounting base PFO83A  
Surface mounting kit Y40 & P3G-08  
Size 58mm x 40mm x 57.5mm



**5 PHILLIPS ST  
THEBARTON S.A. 5031**

**PH (08) 8234 1207  
FAX (08) 8234 1206  
EMAIL [eltron@bigpond.net.au](mailto:eltron@bigpond.net.au)**



## **ONLY TIMERS RANGE**

### **AH3-RE MULTI RANGE**

#### **Features**

Multiple time ranges

Programmable by dip switches

Time ranges from 3 minutes to 30 hours

24/240V AC/DC operating voltage

One timed and one user selectable set of contacts

Supplied with Base, Surface mounting kit available [Y40]

#### **Description**

Full time range 3m, 30m, 3h, 30h, Rated voltage 24 to 240 volts AC/DC

Contact rating 5 Amps AC resistive, Reset time 0.2 seconds, Power consumed 2VA, Mounting base PFO83A, Surface mounting kit Y40 & P3G-08, Size 58mm x 40mm x 57.5mm



### **TRD-N Star Delta Transition Timer**

#### **Features**

Adjustable run time up to 30 seconds

Star to delta change time 0.1 second

Available in either 240 or 415V AC

Two indicating lamps for timer status

#### **Description**

Time range 0-30 seconds,

Rated voltage 240 to 415 volts AC

Contact rating 5 Amps resistive, Change over time 0.1 seconds

Reset time 0.3 seconds

Base 8PFA

Size 61mm x 49mm x 70mm



**5 PHILLIPS ST  
THEBARTON S.A. 5031**

**PH (08) 8234 1207  
FAX (08) 8234 1206  
EMAIL [eltron@bigpond.net.au](mailto:eltron@bigpond.net.au)**





## WIRING DIAGRAMS

CONNECTION :

2C, Mode A

1A1C, Mode B

**AH5N**





CONNECTION :

2C, Mode A

1A1C, Mode B

**AH3-R\***




CONNECTION :

N Type


CONNECTION :

AH5F

**TRD-N**



**AH5F**



**CALL ELTRON TODAY  
FOR ALL YOU'RE  
ONLY NEEDS**

**5 PHILLIPS ST  
THEBARTON S.A. 5031**

**PH (08) 8234 1207  
FAX (08) 8234 1206  
EMAIL [eltron@bigpond.net.au](mailto:eltron@bigpond.net.au)**

